|    | Title   | Current OR | Current XRef  |
|----|---|------------|---|
| 1  | Self contained, independent, in-vacuum spinner motor  | 118/698    | 118/729;<br>118/730;<br>204/298.23;<br>204/298.28;<br>310/89;<br>318/139;<br>318/16;<br>318/3                     |
| 2  | Wheel drum structure of inner stator portion with inbuilt switches  | 310/67A    | 310/68A;<br>310/68R;<br>310/89  |
| 3  | Wheel drum structure of inner stator portion with an inbuilt driving control circuit  | 310/254    | 310/67R;<br>310/68R;<br>310/89  |
| 4  | Servo motor assembly and method of making same  | 310/89     | 310/71  |
| 5  | Device for thermally protecting elastomeric components, system of such devices for the protection of a rotorcraft rotor in cold weather, and rotorcraft rotor equipped with such a system |            | 310/43;<br>310/65;<br>310/85;<br>310/88;<br>310/89;<br>310/91   |
| 6  | Motor and method for producing the same   | 310/89     | 310/254;<br>310/43;<br>310/67R;<br>310/68A;<br>310/68B;<br>310/68C;<br>310/68E;<br>310/68R;<br>310/71;<br>310/75A |
| 7  | Flywheel with electrically controlled input and output  | 310/74     | 310/178;<br>310/89;<br>74/572   |
| 8  | Device for cooling a motor in a climate control system  | 310/52     | 310/57 <b>;</b><br>310/89   |
| 9  | Cap mounted drive for a<br>brushless DC motor   | 310/89     | 310/64;<br>310/68R;<br>318/254  |
| 10 | DC motor drive with improved thermal characteristics  | 310/58     | 310/68A;<br>310/68B;<br>310/68C;<br>310/68D;<br>310/68R;<br>310/89;<br>310/91                                     |

|    | Title  | Current OR | Current XRef   |
|----|--|------------|--|
| 11 | Motor structure  | 310/257    | 310/49R;<br>310/89;<br>360/99.08   |
| 12 | Blower motor housing   | 310/89     | 417/360  |
| 13 | Motorized reduction gear unit, especially for driving a vehicle screen wiper apparatus | 310/85     | 310/68R;<br>310/71;<br>310/83;<br>310/88;<br>310/89                                      |
| 14 | Actuator device for an electric window winder  | 310/68R    | 310/64;<br>310/89;<br>49/337   |
| 15 | Rotary actuator for variable damping force shock absorber                              | 188/282.2  | 188/316;<br>251/129.11;<br>310/156.32;<br>310/89   |
| 16 | Multiply compartmented dynamoelectric machine  | 310/89     | 417/423.14   |
| 17 | End cap for an actuator  | 310/88     | 310/89   |
| 18 | Multiple compartmented dynamoelectric machine  | 310/89     | 310/42   |
| 19 | Power and control chamber for dynamoelectric machines                                  | 310/89     | 310/64   |
| 20 | Pressure washer  | 310/68A    | 310/89;<br>310/91  |
| 21 | Air cooled electromechanical drive apparatus   | 310/63     | 165/80.3;<br>310/89;<br>361/697  |
| 22 | Brushless direct current<br>motor with inverted magnet<br>clip                         | 310/67R    | 29/598;<br>310/42;<br>310/46;<br>310/68B;<br>310/89;<br>310/90;<br>360/99.08;<br>361/212 |
| 23 | Shaft transducer having DC output proportional to angular velocity                     | 310/171    | 310/154.02;<br>310/154.25;<br>310/68B;<br>310/89;<br>335/222                             |